CE

RIKA Innovative Ofentechnik GmbH
AT-4563 Micheldorf, Müllerviertel 20
2025
90-CPR-07.2013

EN14785:2006

Notified Body:	51
Intended use:	Space heating in residential buildings without possible supply of hot water
Name:	INDUO III PELLET
Descriptioin:	space heating appliances fired by wood pellets - system 3

Height		1145 mm
Width		855 mm
Depth		500 mm
Fire safety		pass
Safety distance to combustible material	rear	100 mm
	sides	100 mm
	top	750 mm
	front	800 mm
	floor	0 mm
Emission of combustion products		pass
CO-Emmision at nominal heat output		< 0,02 %
CO-Emmision at nominal heat output		< 0,25 g/Nm^3
Release of dangerous substances		NPD
Surface temperature		pass
Electrical safety		pass
Cleanability		pass
Durability		pass
Mechanical resistance (to carry chimney)		NPD
Maximum operating pressure		not applicable
Flue gas temperature at the measuring section at nominal heat output		164 °C
Flue gas temperature outlet at nominal heat output		189 °C
Thermal output		pass
Nominal- / part load heat output	10,0 kW	3,0 kW
Nominal- / part load space heat output	10,0 kW	3,0 kW
Nominal- / part load water heat get output folder path	not applicable	not applicable
Efficiency		pass
Nominal- / part load Efficiency	91,4 %	91,5 %
recommended fuel type	wood pellets (ISO 17225-2)	
Suitability for installation to a shared flue system		yes
Emission (addition)		
CO wood pellets	g/Nm^3	< 0,25
PM wood pellets	g/Nm^3	< 0,02
OGC wood pellets	g/Nm^3	< 0,06
NO_x wood pellets	g/Nm^3	< 0,20

Pleas read manufacturer´s operating instructions carefully before installing and using the appliance!

RIKA
Innovative Ofentechnik GmbH
A-4563 Micheldorf, Müllerviertel 20
Tel.: +43 (0)7582/686-14, Fax DW: -43
www.rika.at

Signed on behalf of the manufacturer

Andreas Bloderer / product manager

Name and function

Micheldorf, 22.04.2025

Place and date of issue