CE

RIKA Innovative Ofentechnik GmbH
AT-4563 Micheldorf, Müllerviertel 20
2025
91-CPR-07.2013

EN13240:2001/A2:2004/AC:2007

Notified Body:	51
Intended use:	Space heating in residential buildings without possible supply of hot water
Name:	INDUO III SCHEITHOLZ
Descriptioin:	space heating appliances fired by wood logs - system 3

Height		1145 mm
Width		855 mm
Depth		500 mm
Fire safety		pass
Safety distance to combustible material	rear	100 mm
	sides	100 mm
	top	750 mm
	front	800 mm
	floor	0 mm
Emission of combustion products		pass
CO-Emmision at nominal heat output		< 0,12 %
CO-Emmision at nominal heat output		< 1,25 g/Nm^3
Release of dangerous substances		NPD
Surface temperature		pass
Electrical safety		pass (*)
Cleanability		pass
Durability		pass
Mechanical resistance (to carry chimney)		NPD
Maximum operating pressure		not applicable
Flue gas temperature at the measuring section at nominal heat output		282,3 °C
Flue gas temperature outlet at nominal heat output		316,3 °C
Thermal output		pass
Nominal- / part load heat output	10,0 kW	5,0 kW
Nominal- / part load space heat output	10,0 kW	5,0 kW
Nominal- / part load water heat get output folder path	not applicable	not applicable
Efficiency		pass
Nominal- / part load Efficiency	81,6 %	75,9 %
recommended fuel type	wood logs	
Suitability for installation to a shared flue system		yes
Emission (addition)		
CO wood logs	g/Nm^3	< 1,25
PM wood logs	g/Nm^3	< 0,04
OGC wood logs	g/Nm^3	< 0,12
NO_x wood logs	g/Nm^3	< 0,20

Pleas read manufacturer´s operating instructions carefully before installing and using the appliance!

(*) only for models with RIKATRONIC

RIKA
Innovative Ofentechnik GmbH
A-4563 Micheldorf, Müllerviertel 20
Tel.: +43 (0)7582/686-14, Fax DW: -43
www.rika.at

Signed on behalf of the manufacturer

Andreas Bloderer / product manager

Name and function

Micheldorf, 22.04.2025

Place and date of issue